



Name	A (in)	B (in)	C (in)	D (in)	Free Area Without Cover (sq in)
4x10	12.0	5.1	9.6	3.6	27.4
4x12	14.0	5.1	11.6	3.6	34.6
4x14	16.0	5.1	13.6	3.6	41.8
6x10	12.0	7.0	9.6	5.6	46.6
6x12	14.0	7.0	11.6	5.6	57.8
6x14	16.0	7.0	13.6	5.6	69.0
8x8	10.2	10.2	7.6	7.6	50.6
8x10	12.1	10.2	9.6	7.6	73
10x10	12.2	12.2	9.6	9.6	85
12x12	14.2	14.2	11.6	11.6	127.4

Material and Finish

Flair Smart Vents are made of galvanized, then powder coated, industry standard steel.

Wired or Wireless

Flair Smart Vents can be powered by industry standard 24Vac or wirelessly with 2 C-Cell batteries which under typical conditions will last for 4 years.

Low Profile

At just 5mm in height, Flair Smart Vents can be installed in ceilings, walls and floors.

For more information on wiring or installation, visit:

flair.co/vent-manual

flair.co/products/vent



Name	A (in)	B (in)	C (in)	D (in)	Free Area Without Cover (sq in)
4x10	12.0	5.1	9.6	3.6	27.4
4x12	14.0	5.1	11.6	3.6	34.6
6x10	12.0	7.0	9.6	5.6	46.6
6x12	14.0	7.0	11.6	5.6	57.8
6x14	16.0	7.0	13.6	5.6	69.0

Material and Finish

Flair Smart Vents are made of galvanized, then powder coated, industry standard steel.

Wired or Wireless

Flair Smart Vents can be powered by industry standard 24Vac or wirelessly with 2 C-Cell batteries which under typical conditions will last for 4 years.

Low Profile

At just 5mm in height, Flair Smart Vents can be installed in ceilings, walls and floors.

For more information on wiring or installation, visit:

flair.co/vent-manual

flair.co/products/vent