



## SPECIFICATION SHEET

### Smart Vents

Flair's **Zoning and Air Balancing solutions** integrate Flair Smart Vents into home HVAC systems to enhance comfort, improve energy efficiency, and enable precise room-level climate control and air balancing.

Size	SKU	UPC
4x10	FLAIRVENT410	868596000206
4x12	FLAIRVENT412	868596000244
4x14	FLAIRVENT414	868596000282
6x10	FLAIRVENT610	868596000213
6x12	FLAIRVENT612	868596000251
6x14	FLAIRVENT614	868596000275
8x10	FLAIRVENT810	850047423139
8x8	FLAIRVENT88	850047423016
10x10	FLAIRVENT1010	850047423023
12x12	FLAIRVENT1212	850047423030

Accessories	SKU	UPC
Flair Puck 2	FLAIRPUCK2001	850047423153
Flair Puck 2 Pro	FLAIRPUCK2001P	850047423160
Bridge	FLAIRBRIDGE001	868596000268
Bridge Pro	FLAIRBRIDGE001P	850047423146
Static Pressure Kit	FLAIRSPK001	850047423177
Smart Vent Covers - Cast Iron Black	4x10: FLAIRGRILL410B	850047423108
	4x12: FLAIRGRILL412B	850047423115
	4x14: FLAIRGRILL414B	850047423122
Smart Vent Covers - Espresso	4x10: FLAIRGRILL410DB	850047423047
	4x12: FLAIRGRILL412DB	850047423054
	4x14: FLAIRGRILL414DB	850047423061
Smart Vent Covers - Caramel	4x10: FLAIRGRILL410LB	850047423078
	4x12: FLAIRGRILL412LB	850047423085
	4x14: FLAIRGRILL414LB	850047423092

## COMPATIBILITY



Fixed Speed Equipment



Variable and Multi-Stage  
Equipment



**Backpressure Protection:**  
Protocols in place that prevent  
too many Smart Vents from  
being closed at once.

## SPECIFICATIONS

**Power:** Wireless | 2 x C (included), Wired | 24 VAC

**Operating Temp Range:** 0°C to 50°C / 32°F to 122°F

**Storage Temp Range:** -10°C to 55°C / 14°F to 131°F

**Operating Humidity:** 5% to 95% RH (non-condensing)

**Color:** White

**Sensors:** Temperature, Pressure

**Radios:** 915 MHz

**Mounting:** Screws (included)


For full wiring diagrams, see [flair.co/wiring](https://flair.co/wiring)



## SPECIFICATION SHEET

# Smart Vents

### MEASUREMENT GUIDE



Size	A (in)	B (in)	C (in)	D (in)	Free Area Without Cover (sq in)
4x10	12.0	5.1	9.6	3.6	27.4
4x12	14.0	5.1	11.6	3.6	34.6
4x14	16.0	5.1	13.6	3.6	41.8
6x10	12.0	7.0	9.6	5.6	46.6
6x12	14.0	7.0	11.6	5.6	57.8
6x14	16.0	7.0	13.6	5.6	69.0
8x10	12.2	10.2	9.6	7.6	65.8
8x8	10.2	10.2	7.6	7.6	50.6
10x10	12.2	12.2	9.6	9.6	85
12x12	14.2	14.2	11.6	11.6	127.4

### MOUNTING HOLES

Smart Vent with Faceplate Removed:



For ceiling and wall installs.

### RESOURCES

**ZONING SOLUTION GUIDE**  
[flair.co/smart-vent-solution-guide](https://flair.co/smart-vent-solution-guide)



**CONTRACTOR SELLING GUIDE**  
[flair.co/selling-guide-zoning](https://flair.co/selling-guide-zoning)



**WIRING GUIDE**  
[flair.co/wiring](https://flair.co/wiring)



### FLAIR ACCESSORIES

#### BRIDGE

A dedicated plug and play networking device.



#### SMART VENT COVERS

2-Way throw pattern available in three sizes: 4x10, 4x12, 4x14.



#### PRO ONLY

#### BRIDGE PRO

Required to monitor static pressure and fan speed.



#### PRO ONLY

#### STATIC PRESSURE KIT

Required to monitor static pressure.

